



- 1.ELECTRICAL TEST:
 1.1. 100% OPEN&SHORT&MISS WIRE TEST;
 1.2. CONDUCTOR RESISTANCE: 1.50hm/M(Max)
 1.3. INSULATION RESISTANCE: 2M(Min)
 1.4. HI-POT: DC 300V 0.01S

L	T
L≤1m	±30mm
1m<L≤5m	±50mm
5m<L≤10m	±100mm
L>10m	±150mm

M12 X CODE 8POLE~RJ45
 Protection level IP67@M12;
 Nominal voltage UN 30V;
 Nominal current IN 0.5A@M12-X CODE;
 Signal type: Ethernet 10Gbps
 Operating temperature: -20°C to +70°C (fixed)
 -15°C to +60°C (flexible)

WIRE CONNECTION

P1	PAIRS	P2	COLOR(568B)
1	---	1	WHITE/ORANGE
2	---	2	ORANGE
3	---	3	WHITE/GREEN
8	---	4	BLUE
7	---	5	WHITE/BLUE
4	---	6	GREEN
5	---	7	WHITE/BROWN
6	---	8	BROWN
SHELL	---	SHELL	DRAIN



5	CABLE LABEL 80*15mm
4	RJ45 PLUG 8P8C PIN GOLD PLATED SHLL SPCC NI-PLATED
3	MOLDED OF BLACK PVC
2	M12 X CODE 8 POLE SHELL,PIN GOLD PLATED;SHELL NI-PLATED
1	CAT.6A (26#(7/0.16BC*FM_PE)*1P+AL)*4P+D+B(128/0.10TC)+CM-PVC JACKET OD6.5±0.2mm

Date	2025 / 05 / 12
Unit	mm
Projection	drawing
Rev	A
File No.	88498

DELOCK®
we move the world

Item no.	81011
Title:	M12 Cable X-coded 8-pin, angled upward plug to RJ45 plug angled downward, 1 m, blue
EAN:	4043619810116