

PINOUT	
P1	P2
1 — RED —	RED — 1
4 — BLACK —	2

Technical Requirements:

1. 100% tested and free from any electrical issues including short circuits, open circuits, poor conduction or insulation defects.


2. Testing conditions:

- A. Conduction resistance: 5Ω (MAX)
- B. Insulation resistance: 2MΩ (MIN)

The plugs shall not have any flow marks, material shortage, shrinkage, discoloration, damaged terminals, deformation or other defects.

91225	20 cm
91226	30 cm
91227	50 cm
91229	70 cm
91231	1 m

NO.	MATERIAL LIST	NAME	LENGTH	QTY	REMARK
5	PVC 45P black color	CONNECTOR		10G	
4	5241 3P WHITE	PLUG		1PCS	
3	5241 phosphor bronze male terminal	TEMINAL		2PCS	
2	USB2.0 A MALE PLUG, iron case nickle plated	PLUG		1PCS	
1	UL2464 2C24AWG(11/0.16TS black+ree) OD3.5 PVC Jacket	WIRE	1000	1PCS	

Date		2025 / 10 / 20	
Unit		mm	
Projection		drawing	
Rev		A	
File No.		88154	
 we move the world		Item no.	91226
		Title:	Fan cable USB 2.0 male to female 3-pin 30 cm
EAN:		4043619912261	