USB Condenser Microphone Omnidirectional for Conferences

Description



Item no. 20672

EAN: 4043619206728

Country of origin: China

Package: Retail Box

This table microphone by Delock is suitable for use in conferences.

Optimal recordings

The microphone has a circle pattern (omnidirectional) and therefore captures the acoustic signal ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Touch mute button & status LED

The touch mute button quickly mutes the microphone. The LED is red when muted and green when recording.

Headphone output

The microphone has a 3.5 mm stereo jack output for connecting headphones or speakers.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.

Technical details

- Connectors:
  1 x USB 2.0 Type-A male
  1 x 3.5 mm 3 pin stereo jack female
- Directivity: omnidirectional
- Sensitivity: -16 dB +/- 3 dB
- Frequency range: 100 Hz - 10 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 65 dB
- Mute-Button
- Status LED
- Cable length: ca. 1.5 m
- Colour: black

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Dimensions (Ø x H): ca. 75 x 19 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Images







All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

General

Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11
LED indicator:	1 x

Interface

Connector:	1 x USB 2.0 Type-A male

Technical characteristics

Frequency range:	100 Hz - 10 kHz
Voltage supply:	USB bus powered
Sensitivity:	-16 dB +/- 3 dB
Sample rate:	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	ca. 65 dB

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Directivity:	omnidirectional

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Physical characteristics

Cable length:	1.5 m
Diameter:	75 mm
Height:	19 mm
LED colour:	red green

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**