Push Button for Installation 12 mm 4 x solder connection LED green power symbol momentary

Description

This push button by Delock is ideal for installation in control panels, for example in industry, control or regulation technology. Push buttons can also be found in the automotive industry or the consumer sector. For example, as doorbells or triggers for lighting systems with timers such as those found in hallways.



Item no. 22011

EAN: 4043619220113

Country of origin: China

Package: Zip poly bag

Button

A so called button, or push button, returns to its initial position after being pressed.

Opener and closer

The NO (closer) contact establishes a connection between two contacts, while the NC (opener) contact releases them.

Please Note

The installation should only be carried out by qualified electricians in compliance with the usual national power supply guidelines.
Grounding is necessary for low-voltage systems to ensure the safety and functionality of the system.

Technical details

- Connectors: 4 x solder connection
- Switch type: 1 closer (NO)
- Load limit: AC 250 V~ / 2 A
- Number of contacts: 4
- Number of open contact: 1
- Function: momentary
- Actuator: flat
- Operating temperature: -30 °C ~ 85 °C
- Mounting hole diameter: ca. 12 mm
- Hexagon nut spanner width: 14 mm
- Mounting depth: ca. 25 mm
- Thread size: M12
- LED lighting: green
- LED voltage: 12 V
- LED type: power symbol
- Material: stainless steel nickel plated

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Mechanical life: 200,000 cycles
- Electrical service life: 100,000 cycles
- Protection class: IP65
- Dimensions (LxD): ca. 23 x 14 mm

Package content

- Push-button
- 1 x rubber ring

Images





All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

General

Mounting type:	Soldering
Protection class:	IP65
LED indicator:	Powersymbol
Style:	momentary

Technical characteristics

Load limit:	AC 250 V~ / 2 A
Operating temperature:	-30 °C ~ 85 °C

Physical characteristics

Housing material:	stainless steel nickel plated
Colour:	silver
Thread type:	M12
LED colour:	green
Mounting hole diameter:	12 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**