Rotary Switch for Installation 22 mm 3 x solder connection switching with anti-twist protection

Description

This switch by Delock is ideal for installation in control panels, for example in industry, control or regulation technology. Push buttons can also be found in the automotive industry or the consumer sector. For example, as doorbells or triggers for lighting systems with timers such as those found in hallways.

Opener and closer

The NO (closer) contact establishes a connection between two contacts, while the NC (opener) contact releases them.



Item no. 22210

EAN: 4043619222100

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
  3 x solder connection
- Switch type: 1 closer (NO) + 1 opener (NC)
- Load limit: AC 250 V~ / 2 A
- Number of contacts: 3
- Function: switching
- Actuator: high
- Anti-twist protection
- Operating temperature: -30 °C ~ 85 °C
- Mounting hole diameter: ca. 22 mm
- Hexagon nut spanner width: 25 mm
- Mounting depth: ca. 37 mm
- Thread size: M22
- Material: stainless steel nickel plated
- Mechanical life: 200,000 cycles
- Electrical service life: 100,000 cycles
- Protection rating: IP65
- Dimensions (LxD): ca. 46 x 25 mm

Package content

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Rotary switch
- 1 x rubber ring

Images







All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

General

Mounting type:	Soldering
Protection class:	IP65
Style:	latching

Technical characteristics

Load limit:	AC 250 V~ / 2 A
Operating temperature:	-30 °C ~ 85 °C

Physical characteristics

Housing material:	stainless steel nickel plated
Colour:	silver
Thread type:	M22

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**