

# Industry Hub 7 x USB 2.0 Type-A with 15 kV ESD protection and DIN rail mounting

## Description

This **solid** industry capable USB Hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by **seven USB Type-A connectors**.

## Screw connection and mounting option

Each USB port has two screw holes with M3 thread. Appropriate **cables can be plugged in and screwed** into the screw holes. This ensures a secure data connection even in mobile environments.

In addition, the hub comes with **wall mounting plates** and a **DIN rail bracket**, making it perfect for installation in an industrial environment.

## ESD fuse

The USB ports are protected against electrostatic discharges up to **15 kV**.

## Power supply

If necessary, an optional power supply or an optional power cable can be connected to the power socket. A voltage between 9 - 36 V can be applied to the terminal power connection, and 5 V to the DC connection.



**Item no. 60687**

EAN: 4043619606870

Country of origin: China

Package: Box

## Technical details

- Connectors:
  - 1 x USB 2.0 Type-B female
  - 7 x USB 2.0 Type-A female
  - 1 x 5 V DC jack
  - 1 x 9 - 36 V 3 pin terminal power connector
- Chipset: Genesys Logic GL850G
- Data transfer rate up to 480 Mbps
- Bootable
- Plug & Play
- 1 x LED indicator
- Robust metal housing
- USB ports with screw holes
- Pitch of screw hole USB Type-A: ca. 19 mm
- Pitch of screw hole USB Type-B: ca. 19.5 mm

- Thread size: M3
- Removable wall-mount brackets
- Power supply: Bus-powered or Self-powered
- Flexible power supply with 9 V to 36 V at the terminal power connection
- ESD protection up to 15 kV for all ports
- Operating temperature: 0 °C ~ 60 °C
- Storage temperature: -10 °C ~ 70 °C
- Colour: black
- Dimensions (LxWxH): ca. 158 x 80 x 32 mm

---

## Specification of power connector

- DC:
- 5 V
- Dimensions:
  - inside:  $\varnothing$  ca. 2.1 mm
  - outside:  $\varnothing$  ca. 5.5 mm
  - length: ca. 9 mm
  - terminal:
- 9 - 36 V

---

## System requirements


- Linux Kernel 6.2 or above
- Mac OS 13.1 or above
- Windows 10/10-64/11
- Windows Server 2022
- PC or laptop with a free USB Type-A port

---

## Package content

- Hub USB
- 1 x cable USB A male to USB B male, length ca. 1.8 m
- 2 x wall mounting brackets
- 1 x mounting for 35 mm DIN rail
- 1 x 3 pin terminal block
- User manual

## Images



## General

|                             |                                                                                                                                  |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Function:                   | bootable                                                                                                                         |
| Supported operating system: | Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 11<br>Windows Server 2022<br>Mac OS 13.1 or above<br>Linux Kernel 6.2 or above |
| LED indicator:              | 1 x                                                                                                                              |

## Interface

|              |                                             |
|--------------|---------------------------------------------|
| Connector 1: | 1 x USB 2.0 Type-B female                   |
| Connector 2: | 7 x USB 2.0 Type-A female                   |
| Connector 3: | 1 x 5 V DC jack                             |
| Connector 4: | 1 x 9 - 36 V 3 pin terminal power connector |

## Technical characteristics

|                        |                      |
|------------------------|----------------------|
| Chipset:               | Genesys Logic GL850G |
| Data transfer rate:    | 480 Mbps             |
| Storage temperature:   | -10 °C ~ 70 °C       |
| Operating temperature: | 0 °C ~ 60 °C         |

## Physical characteristics

|                   |        |
|-------------------|--------|
| Housing material: | metal  |
| Length:           | 158 mm |
| Width:            | 80 mm  |
| Height:           | 32 mm  |
| Colour:           | black  |

### Manufacturer information

Street Beeskowdamm 13/15  
 Postal code 14167  
 City Berlin  
 Country Deutschland  
 E-Mail [info@delock.de](mailto:info@delock.de)  
 Website [www.delock.de](http://www.delock.de)

