

Network Surge Protector RJ45

Description

This surge protector by Delock reliably protects sensitive network devices against power surges and electrostatic discharges. Its robust design and simple inline installation make it ideal for PoE cameras, routers, switches, or other Ethernet components. The integrated protection circuit safely diverts dangerous surges, ensuring a stable and safe network connection.



Item no. 62061

EAN: 4043619620616

Country of origin: China

Package: White Box


Technical details

- Connectors:
 - 1 x RJ45 jack (device)
 - 1 x RJ45 jack (external)
 - 1 x cable lug for equipotential bonding
- SPD class: Type 2, LPZ 0B-2 or higher
- Max. continuous voltage (PoE) 57 V-
- Nominal current 1 A
- C2 Nominal discharge current (8/20) 10 kA
- Cut-off frequency 250 MHz
- Data transfer rate up to 10/100/1000 Mbps
- Cat.6 specification
- Supports PoE devices
- Operating temperature: -40 °C ~ 80 °C
- Housing material: metal
- Dimensions (LxWxH): ca. 83.0 x 25.5 x 25.5 mm

Package content

- Network Surge Protector
- Network cables, length ca. 30 cm
- User manual

Images



General

Specification:	Cat. 6 PoE Power over Ethernet
----------------	-----------------------------------

Interface

Connector 1:	1 x RJ45 jack
Connector 2:	1 x RJ45 jack

Technical characteristics

Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps
Operating temperature:	-40 °C ~ 80 °C

Physical characteristics

Housing material:	metal
Length:	83 mm
Width:	25.5 mm
Height:	25.5 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de

Website

www.delock.de

