

Network Surge Protector RJ45 outdoor IP67 DIN rail mounting

Description

This surge protector by Delock reliably protects sensitive network devices against power surges and electrostatic discharges. Its robust design and simple inline installation make it ideal for PoE cameras, routers, switches, or other Ethernet components. The integrated protection circuit safely diverts dangerous surges, ensuring a stable and safe network connection.



Item no. 62065

EAN: 4043619620654

Country of origin: China

Package: White Box

Technical details

- Connectors:
 - 1 x RJ45 jack (device)
 - 1 x RJ45 jack (external)
 - 1 x screw terminal for equipotential bonding
- SPD class: Type 2, LPZ 0B-2 or higher
- Max. continuous voltage (PoE) 57 V-
- Nominal current 1 A
- C2 Nominal discharge current (8/20) 10 kA
- Cut-off frequency 500 MHz
- Data transfer rate up to 10/100/1000 Mbps
- Cat.6 specification
- Supports PoE devices
- Operating temperature: -40 °C ~ 80 °C
- Protection rating: IP67
- Housing material: metal
- Dimensions (LxWxH): ca. 173 x 39 x 30 mm

Package content

- Network Surge Protector
- User manual

Images



General

Mounting type:	DIN rail 35 mm
Specification:	Cat. 6 PoE Power over Ethernet
Protection class:	IP67

Interface

Connector 1:	1 x RJ45 jack
Connector 2:	1 x RJ45 jack

Technical characteristics

Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps
Operating temperature:	-40 °C ~ 80 °C

Physical characteristics

Housing material:	metal
Length:	174 mm
Width:	39 mm
Height:	30 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

