M8 A-coded 3 pin Serial Connection Cable with FTDI chipset, USB 2.0 Type-A male to M8 RS-232 male 1.8 m black

Description

This **serial USB 2.0 to M8 RS-232 cable** by Delock can be used for the **industrial application** e.g. for **sensors** and **automation modules**.



Item no. 64258

EAN: 4043619642588

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
  1 x USB 2.0 Type-A male
  1 x M8 RS-232 male A-coded 3 pin
- Chipset: FTDI FT231 X
- Signals: TXD(1), RXD(3), GND(4)
- Cable gauge: 24 AWG
- Cable diameter: ca. 5.0 mm
- Cable jacket material: PVC
- Colour: black
- Cable length: ca. 1.8 m

System requirements

- Linux Kernel 5.8 or above
- Mac OS 10.15.7 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port
- A free M8 RS-232 port

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Package content

- Serial cable

Images





All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Interface

Connector 1:	1 x USB Type-A male
Connector 2:	1 x M8 RS-232 male A-coded 3 pin

Physical characteristics

Cable length:	1.8 m
Cable gauge:	24 AWG
Material:	PVC
Colour:	black
Cable diameter:	5 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**