USB Condenser Microphone Set - for Podcasting, Gaming and Vocals

Description

This USB condenser microphone by Delock can be used for high-quality voice and vocal recordings.

Optimal recordings

The microphone has a cardioid polar pattern (unidirectional) and captures the sound ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Dual Layer Pop Filter & Windscreen

Due to the included dual layer pop filter and the windscreen, the recording quality is further optimized. Annoying wind noises are optimally filtered.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.

Stable & non-slip stand

The metal base with rubber feet ensures that the microphone stands stable on the table. The shock mount (spider) ensures vibration-free recording. The table stand can be folded and transported easily if required.



Item no. 66331

EAN: 4043619663316

Country of origin: China

Package: Retail Box

Technical details

- Connector: 1 x USB 2.0 Type-A male
- Directivity: unidirectional
- Sensitivity: -47 dB +/- 3 dB
- Frequency range: 20 Hz - 20 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 60 dB
- Impedance: 2.2 kOhm
- Cable length: ca. 1.5 m

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Colour: black
- Dimensions (LxWxH): ca. 150 x 45 x 35 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- Table stand
- Shock mount (spider)
- Pop filter
- Windscreen
- User manual

Images



All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

General

Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

Connector:	1 x USB 2.0 Type-A male

Technical characteristics

Frequency range:	20 Hz - 20 kHz
Voltage supply:	USB bus powered
Sensitivity:	-47 dB +/- 3 dB
Sample rate:	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	ca. ≥ 60dB
Directivity:	uni-directional

Physical characteristics

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Cable length:	1.5 m
Length:	150 mm
Width:	45 mm
Height:	35 mm
Colour:	black

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**