USB Microphone with Gooseneck and Mute Button

Description

This USB microphone by Delock can be used for voice and vocal transmissions.

Optimal recordings

The microphone has a cardioid polar pattern (unidirectional) and captures the sound ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Mute button & LED ring

With the mute button in the middle of the microphone, the microphone can be quickly muted. The LED ring signals operational status with a blue or red light.

Flexible gooseneck

With the gooseneck, the microphone can be bent in the preferred direction.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.



Item no. 66499

EAN: 4043619664993

Country of origin: China

Package: Retail Box

Technical details

- Connector: 1 x USB 2.0 Type-A male
- Directivity: unidirectional
- Sensitivity: -35 dB +/- 3 dB
- Frequency range: 70 Hz - 15 kHz
- Sample rate: 16 Bit / 48 kHz
- Mute-Button
- Gooseneck, length ca. 7 cm
- Status LED
- Dimensions (LxWxH): ca. 196 x 23 x 23 mm
- USB bus powered

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 3.3 or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Images







All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

General

Function:	Plug & Play
Specification:	USB 2.0
Supported operating system:	Chrome OS Linux Kernel 3.3 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	1 x

Interface

Connector:	1 x USB 2.0 Type-A male

Technical characteristics

Frequency range:	70 Hz - 15 kHz
Voltage supply:	USB bus powered
Sensitivity:	-35 dB +/- 3 dB
Sample rate:	16 Bit / 48 kHz
Directivity:	uni-directional

Physical characteristics

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Length:	196 mm
Width:	23 mm
Height:	23 mm
LED colour:	red blue

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**