USB Tie Lavalier Microphone Omnidirectional 24 bit / 192 kHz with clip and 3.5 mm stereo jack headphone port

Description

This USB microphone by Delock can be used for high-quality voice and vocal transmissions.



Item no. 66638

EAN: 4043619666386

Country of origin: China

Package: Retail Box

With clip to attach
It can easily be **clipped** to a **tie** or **collar**.

Optimal recordings
The microphone has a **circle pattern** (**omnidirectional**) and therefore captures the acoustic signal ideally. Due to a high performance, low self-noise and precise performance, even the finest sounds are optimally recorded.

High sampling rate
Typical USB microphones work with 16 Bit and 44 kHz. This Delock microphone offers a sampling rate of **24 bit** and **192 kHz**, so it is possible to record in **Hi-Fi studio quality**.

High-Res audio headphone output
The microphone has a **3.5 mm stereo jack** female port for connecting e.g. headphones or loudspeakers, for example. The audio output provides a bit depth of **32 bits** at a **sampling rate** of **192 kHz.**

Plug & Play
Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as **Windows**, **Mac OS**, **Chrome OS** and **Linux**.

Technical details

- Connectors:

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

1 x USB 2.0 Type-A male
1 x 3.5 mm 3 pin stereo jack female

- Directivity: omnidirectional
- Sensitivity: -30 dB +/- 3 dB
- Frequency range: 50 Hz - 18 kHz
- Sampling rates:
  recording up to 24 bit / 192 kHz
  playback up to 32 bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 74 dB
- Cable length: ca. 2 m
- Housing material: metal
- Colour: black / anthracite
- Weight: ca. 30 g
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 3.3 or above
- Mac OS 10.14 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- Clip
- Windscreen
- Storage bag
- User manual

Images







All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

General

Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 3.3 or above Mac OS 10.14 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11

Interface

Connector 1:	1 x 3.5 mm 3 pin stereo jack female 1 x USB 2.0 Type-A male

Technical characteristics

Frequency range:	50 Hz - 18 kHz
Voltage supply:	USB bus powered
Sensitivity:	-30 dB +/- 3 dB
Sample rate:	24 Bit / 192 kHz
Signal noise ratio (SNR):	ca. 74 dB
Directivity:	omnidirectional

Physical characteristics

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Weight:	30 g
Cable length:	2 m
Colour:	anthracite black

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**