Professional Computer Podcasting Microphone with XLR connector and 3 pin stereo jack male + adapter cable for Smartphone and Tablet

Description

This professional condenser microphone by Delock can be used for high-quality voice and vocal recordings.

Optimal recordings

The microphone has a high-quality **16 mm condenser chip** and a **cardioid polar pattern** (**unidirectional**) and therefore ideally captures the sound. Due to high power, low self-noise and precise performance, even the finest sounds are recorded crystal clear.

Good windscreen

Due to the included windscreen, the recording quality is further optimized. Disturbing wind noises are optimally filtered.

Multifunctional application

It can be connected to any PC or laptop via the**detachable XLR** to **3 pin stero jack cable**. With the **included 4 pin Y-adapter cable**, it can also be connected to a tablet or smartphone.

Stable & non-slip stand

The metal stand with rubber feet ensures that the microphone stands stable on the table. The microphone holder can be adjusted in a 180° angle as required. The table stand can be easily folded and transported when needed.



Item no. 66640

EAN: 4043619666409

Country of origin: China

Package: Retail Box

Technical details

- Connector: 1 x XLR plug
- Cable:
  1 x XLR jack >
  1 x 3.5 mm 3 pin stereo jack male
- Y-Adapter:
  1 x 3.5 mm 4 pin stereo jack male (CTIA standard) >
  1 x 3.5 mm 3 pin stereo jack female microphone
  1 x 3.5 mm 3 pin stereo jack female headset

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Directivity: unidirectional
- Sensitivity: -38 dB +/- 3 dB
- Frequency range: 30 Hz - 16 kHz
- Signal-to-noise ratio (SNR): ca. 70 dB
- Self-Noise: max. 16 dBA
- Sound pressure level (SPL): max. 120 dB
- Cable length: ca. 2.5 m
- Colour: black
- Voltage: 1.5 V

System requirements


- A free stereo port 3.5 mm

Package content

- XLR microphone
- XLR to stereo jack cable
- Y-adapter cable
- Windscreen
- Microphone holder
- Table stand

Images



All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Interface

Connector:	1 x XLR Male
Connector 1:	1 x XLR jack
Connector 2:	1 x 3.5 mm 3 pin stereo jack male

Technical characteristics

Frequency range:	30 Hz - 16 kHz
Voltage supply:	1.5 V
Sensitivity:	-38 dB +/- 3 dB
Signal noise ratio (SNR):	ca. 70 dB
Directivity:	uni-directional

Physical characteristics

Housing material:	metal
Cable length:	2.5 m
Colour:	black

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**