# USB Condenser Microphone with Stand 24 Bit / 192 kHz for PC and Laptop

## Description

This USB condenser microphone by Delock can be used for high-quality voice and vocal recording, making it suitable for **streaming, podcasting, gaming** and **video meetings.**

### Optimal recordings

The microphone has a **cardioid polar pattern (unidirectional)** and captures the sound ideally. Due to a high performance, low self-noise and precise reproduction, even the finest sounds are optimally recorded.

### High resolution sampling rate

Typical USB microphones work with 16 Bit and 44 kHz. The Delock microphone offers a sampling rate of **24 Bit** and **192 kHz**, so that recordings in **high-resolution HiFi studio quality** are possible.

### Stepless microphone gain

The microphone gain control allows you to individually increase or decrease the volume of the microphone recording.

### Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as **Windows, Mac OS, Chrome OS** and **Linux.**

### Stable & non-slip stand

The metal base with rubber feet ensures that the microphone stands stable on the table. The tripod table stand can be folded and transported easily if required.



**Item no. 66832**

EAN: 4043619668328

Country of origin: China

Package: Retail Box

## Technical details

- Connector: 1 x USB 2.0 Type-B female
- Directivity: unidirectional

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Sensitivity: -13 dB +/- 3 dB
- Frequency range: 20 Hz - 20 kHz
- Sample rate: 24 Bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 60 dB
- Sound pressure level (SPL): max. 93 dB
- Cable length: ca. 1.5 m
- USB bus powered
- Plug & Play

## System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB microphone
- USB 2.0 Type-A to USB 2.0 Type-B cable
- Table stand (tripod)
- Microphone installation ring
- User manual

## Images








All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. © **2026 by Delock. All rights reserved.**

## General

| | |
|---|---|
| Function: | Plug & Play |
| Supported operating system: | Chrome OS<br>Linux Kernel 4.4 or above<br>Mac OS 10.9 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |

## Interface

| | |
|---|---|
| Connector: | 1 x USB 2.0 Type-A male<br>1 x USB 2.0 Type-B male |
| Input: | 1 x USB 2.0 Type-B female |

## Technical characteristics

| | |
|---|---|
| Frequency range: | 20 Hz - 20 kHz |
| Voltage supply: | USB bus powered |
| Sensitivity: | -13 dB +/- 3 dB |
| Sample rate: | 24 Bit / 176 kHz |
| Signal noise ratio (SNR): | ca. 60 dB |
| Directivity: | uni-directional |

## Physical characteristics

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

| | |
|---|---|
| Cable length: | 1.5 m |
| Colour: | black |

## Manufacturer information


| | |
|---|---|
| Street | Beeskowdamm 13/15 |
| Postal code | 14167 |
| City | Berlin |
| Country | Deutschland |
| E-Mail | info@delock.de |
| Website | www.delock.de |


All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**