Professional USB Condenser Microphone 24 Bit / 192 kHz for PC and Laptop

Description

This professional USB condenser microphone by Delock can be used for high-quality voice and vocal recording, making it suitable for streaming, podcasting, gaming and video meetings.

Optimal recordings

The microphone has a **16 mm condenser** and a **cardioid polar pattern (unidirectional)** and therefore ideally captures the sound. Due to high power, low self-noise and precise performance, even the finest sounds are recorded crystal clear.

High resolution sampling rate

Typical USB microphones work with 16 Bit and 44 KHz. The Delock microphone offers a sampling rate of **24 Bit** and **192 kHz**, so it is possible to record in **Hi-Fi studio quality.**

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as **Windows, Mac OS, Chrome OS and Linux.**

Stable & non-slip stand

The metal base with rubber feet ensures that the microphone stands stable on the table. The tripod table stand can be folded and transported easily if required.



Item no. 66882

EAN: 4043619668823

Country of origin: China

Package: Retail Box

Technical details

- Connector: 1 x USB 2.0 Type-B female
- Directivity: unidirectional
- Sensitivity: -38 dB +/- 3 dB
- Frequency range: 30 Hz - 16 kHz
- Sample rate: 24 Bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 70 dB
- Self-Noise: max. 16 dBA

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Sound pressure level (SPL): max. 120 dB
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- USB 2.0 Type-A to USB 2.0 Type-B cable, length ca. 2.5 m
- Table stand (tripod)
- Microphone installation ring
- Windscreen
- User manual

Images



All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

General

Function:	Plug & Play
Specification:	USB 2.0
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

Connector:	1 x USB 2.0 Type-A male 1 x USB 2.0 Type-B male
Input:	1 x USB 2.0 Type-B female

Technical characteristics

Frequency range:	30 Hz - 16 kHz
Voltage supply:	USB bus powered
Sensitivity:	-38 dB +/- 3 dB
Sample rate:	24 Bit / 192 kHz
Signal noise ratio (SNR):	ca. 70 dB
Directivity:	uni-directional

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Physical characteristics

Cable length:	2.5 m
Colour:	black

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**