

SMA jack 90° on printed circuit board thread length 5 mm

Description

The SMA jack connector by Delock is suitable for soldering on circuit boards. The gold coating prevents corrosion and ensures an optimal connection.



Item no. 67410

EAN: 4043619674107

Country of origin: China

Package: Zip poly bag

Technical details

- Connector: 1 x SMA jack 90°
- Frequency range: DC - 6 GHz
- Pin: copper gold plated
- Housing: copper gold plated
- Impedance: 50 Ohm
- VSWR: < 1.5
- Insulator: PTFE
- Insulation resistance: > 500 MOhm
- Mating Cycles: > 500
- Mounting type: through-hole mounting
- Soldering: 5 solder points
- Operating temperature: -55 °C ~ 165 °C
- Withstanding voltage: 1000 V / 50 Hz
- Thread type: 1/4" - 36 UNS - 2A
- Thread length: 5 mm
- Dimensions (LxWxD): ca. 17.0 x 13.0 x 6.0 mm

Package content

- SMA Jack

General

Mounting type:	THT solder assembly (Through-hole mounting)
----------------	---

Interface

Connector:	1 x SMA Jack 90°
------------	------------------

Technical characteristics

Frequency range:	0 - 6 GHz
Impedance:	50 Ω
Operating temperature:	-55 °C ~ 165 °C
VSWR:	< 1.5

Physical characteristics

Solder pin:	Ø 1.5 mm
Housing material:	copper gold plated
Thread length:	5 mm
Pin finishing:	copper gold plated
Length:	17 mm
Width:	13 mm

Height:	6 mm
Thread type:	1/4" - 36 UNS - 2A
Insulator:	PTFE

Manufacturer information

Street Beeskowdamm 13/15
 Postal code 14167
 City Berlin
 Country Deutschland
 E-Mail info@delock.de
 Website www.delock.de

