D-Tap Coiled Cable to USB Type-C™ male 1 m

Description

This D-Tap cable by Delock enables camera and video equipment to be powered via a professional camera battery. The D-Tap plug connects directly to a battery or another power source with a D-Tap connector. At the other end is a USB Type-C™ connector, which can be used to power compatible devices such as cameras, monitors, video lights and other accessories.



Coiled Cable

The coiled cable ensures stable data transmission and can be stored in a space-saving manner. Thanks to its coiled design, it takes up less space than conventional cables and remains compact even when not in use. If required, it can be extended to up to four times its original length and then retracts reliably.

Item no. 67692

EAN: 4043619676927

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
  1 x D-Tap 2 pin male
  1 x USB Type-C™ male
- Cable gauge: 20 AWG
- Rated voltage: 300 V
- Current: max. 6.5 A
- Operating voltage: 30 V
- USB Type-C™ supports up to ca. 48 V / 3 A
- Coiled Cable
- Coiled length:
  min.: 140 mm
  max.: 920 mm
- Expansion ratio: 4:1
- Cable diameter: ca. 4.0 mm
- Cable jacket material: TPU
- Colour: black
- Length incl. connectors: ca. 1 m

Package content

- D-Tap coiled cable

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Images



All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Interface

Connector 1:	1 x D-Tap 2 pin male
Connector 2:	1 x USB Type-C™ male

Physical characteristics

Cable gauge:	20 AWG
Material:	TPU
Length:	1 m
Cable diameter:	4.0 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**