USB Type-C™ Network Adapter 10 Gigabit LAN 1 x RJ45 with Power Delivery PD 3.1 140 watt

High speed: Data transfer rates up to 10 Gbps

This USB network adapter by Delock offers a reliable and fast network connection. With a transmission speed of up to 10 gigabits per second, it enables efficient working and smooth streaming.

USB Power Delivery (USB PD 3.1) support up to 140 watt

The adapter has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it.

Compact and lightweight design

The compact and lightweight design makes the adapter ideal for use on the go or in the office. It also ensures a stable and secure network connection with consistent performance. The adapter is compatible with Windows, Mac OS and Linux, making it very versatile.

NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps, 2,5 Gbps, 5 Gbps and 10 Gbps with conventional networking cables. The best possible transmission rate is set automatically.



Item no. 81629

EAN: 4043619816293

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
  1 x USB 20 Gbps USB Type-C™ male
  1 x 10 Gigabit LAN RJ45 jack
  1 x USB Type-C™ Power Delivery female
- Chipset: Realtek RTL8159
- Output power PD for host: max. 140 W
- Data transfer rate:
  Ethernet up to 10 Mbps
  Fast Ethernet up to 100 Mbps
  Gigabit Ethernet up to 1000 Mbps
  NBASE-T with up to 2.5 Gbps and 5 Gbps
  10 Gigabit Ethernet up to 10 Gbps
- Supports IEEE 802.3, 802.3u, 802.3ab
- Supports IEEE 802.3bz: 2.5 / 5GBASE-T
- Supports IEEE 802.3an: 10GBASE-T
- Supports IEEE 802.3az (Energy Efficient Ethernet)

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Supports IEEE 802.1P layer 2 priority encoding
- Supports IEEE 802.3x full duplex flow control
- Supports 16k Jumbo Frames
- LED indicator for link and activity
- USB bus powered
- Robust aluminum housing
- Colour: anthracite
- Cable length without connectors: ca. 20 cm
- Dimensions (LxWxH): ca. 96 x 34 x 15 mm

System requirements

- Linux Kernel 6.14 or above
- Mac OS 15.6.1 or above
- Windows 11
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3/4/5 port

Package content

- USB Type-C™ 10 Gigabit LAN adapter
- User manual

Images





All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

General

Specification:	USB 20 Gbps
Supported operating system:	Windows 11 Linux Kernel 6.14 or above Mac OS 15.6.1 or above
LED indicator:	Link and activity

Interface

Connector 1:	1 x USB 20 Gbps USB Type-C™ male
Connector 2:	1 x Gigabit LAN RJ45 jack
Connector 3:	1 x USB Type-C™ Power Delivery female

Technical characteristics

Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps Gigabit Ethernet up to 2.5 Gbps Gigabit Ethernet up to 5 Gbps Gigabit Ethernet up to 10 Gbps

Physical characteristics

Housing material:	Aluminium
Cable length:	20 cm
Length:	96 mm

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Width:	34 mm
Height:	15 mm
Colour:	anthracite

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**