

USB 2.0 Slot Bracket with 2 x EASY USB Type-A Port

Description

This slot bracket by Delock expands the PC by two USB 2.0 Type-A female ports. The cable of the slot bracket can be connected internally to the motherboard with a 9 pin USB 2.0 pin header male. Thus, the internal connection will be lead outside, in order to connect devices with USB Type-A connector to the computer.

User-friendly reversible EASY USB female ports

The EASY USB sockets are twist-proof and can be used on both sides, so there is no need to pay attention to the correct top or bottom side when inserting a plug.



Item no. 91800

EAN: 4043619918003

Country of origin: China

Package: Box

Technical details

- Connectors:
 - internal:
 - 1 x 9 pin pin header female
 - external:
 - 2 x USB 2.0 Type-A reversible female
- USB Type-A female usable in both directions
- Pitch: 2.54 mm
- Screw type: #4-40 UNC
- Cable gauge:
 - 28 AWG data line
 - 24 AWG power line
- Cable diameter: ca. 4.3 mm
- Gold-plated connector
- Cable double shielded
- Voltage: max. 5 V
- Current: max. 500 mA
- Data transfer rate up to 480 Mbps
- Cable colour: black
- Cable length: ca. 30 cm

System requirements

- PC with one free slot

- Motherboard with a free 9 pin USB 2.0 pin header male

Package content

- Slot bracket

General

Specification:	USB 2.0
Style:	EASY-USB

Interface

Connector 1:	1 x 9 pin USB 2.0 pin header female
Connector 2:	2 x USB Type-A female

Technical characteristics

Data transfer rate:	480 Mbps
Maximum current:	500 mA
Voltage:	5 V

Physical characteristics

Pitch distance:	2.54 mm
Cable colour:	black
Cable length incl. connectors:	30 cm
Pin finishing:	gold-plated
Cable gauge:	28 AWG data line 24 AWG power line
Screw type:	#4-40 UNC
Shielding:	double
Cable diameter:	4.3 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

