

PCI Express x4 Card to 4 x USB 10 Gbps USB Type-A Dual Channel

Description

The PCI Express card by Delock expands a PC by **four external USB 10 Gbps ports**. Different USB devices such as USB flash memory, card reader, external enclosure etc. can be connected. A maximum **data transfer rate of up to 10 Gbps** can be reached.

Dual channel

The card has two ASM3142 chipsets each for two USB Type-A connectors. This ensures the high data transfer rate of 10 Gbps on all ports when used at the same time.



Item no. 91847

EAN: 4043619918478

Country of origin: Taiwan,
Republic of China

Package: Box

Technical details

- Connectors:
external:
4 x USB 10 Gbps Type-A female
internal:
1 x PCI Express x4, V3.0
1 x SATA 15 pin power connector
1 x 4 pin power connector
- Chipset: Asmedia ASM3142, Pericom PI7C9X3G808GP
- Data transfer rate up to 5 Gbps
- Electrical power per port: max. 4.5 watt (5 V / 900 mA)
- Bootable
- Supports UASP
- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports Multiple INs
- USB ports with screw holes (M2 x 0,4)
- IOI item number: U31X2-PCIE4XG322

System requirements

- Linux Kernel 6.14 or above

- Windows 10/10-64/11
- Windows Server 2022
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content

- PCI Express card USB 10 Gbps
- User manual

Images



General

Function:	bootable UASP
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 11 Windows Server 2022 Linux Kernel 6.14 or above

Interface

External:	4 x USB 10 Gbps Type-A female
Internal:	1 x PCI Express x4, V3.0 1 x 4 pin power connector 1 x SATA 15 pin power connector

Technical characteristics

Electrical power per port:	USB Type-A: max. 4.5 watt (5 V / 0.9 A)
Chipset:	Asmedia ASM3142 Pericom PI7C9X3G808GP
Data transfer rate:	5 Gbps

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

