

# Delock LTE / GSM / UMTS Antenna SMA plug 3 dBi fixed omnidirectional with magnetic base and connection cable RG-174 2 m outdoor black

## Description

This antenna by Delock allows the usage of different LTE, GSM and UMTS bands inside and outside. It is completely compatible to Bluetooth, WLAN 2.4 GHz, ZigBee, DECT, Z-Wave and LoRa 868 MHz / 915 MHz.



2 m

## Specification

- Connector: 1 x SMA plug
- Frequency range:  
800 - 960 MHz  
1710 - 2700 MHz
- GSM, UMTS, Bluetooth, WLAN 2.4 GHz, ZigBee, DECT, Z-Wave, LoRa 868 MHz / 915 MHz
- Antenna gain: 3 dBi
- Impedance: 50 Ohm
- Polarisation: vertical
- VSWR: 2.0
- Operating temperature: -30 °C ~ 70 °C
- Colour: black
- Antenna length including magnetic base: ca. 88.7 mm
- Cable: coaxial
- Cable type: RG-174
- Cable colour: black
- Cable loss: 1.5 dB @ 1.5 GHz per meter
- Cable diameter: ca. 2.7 mm
- Cable length incl. connector: ca. 2 m
- Diameter magnetic base: ca. 29.0 mm

## System requirements

- Device with a free SMA jack

## Package content

- Antenna



## Item no. 12416

EAN: 4043619124169


Country of origin: Taiwan, Republic of China

Package: Poly bag


Images




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 170000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 217000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 200000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 200000 Hz  
Polarization: E-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 170000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%




SR: A-4002, MATERIAL: 40P  
Frequency: 100000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%



SR: A-4002, MATERIAL: 40P  
Frequency: 217000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%



SR: A-4002, MATERIAL: 40P  
Frequency: 200000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%



SR: A-4002, MATERIAL: 40P  
Frequency: 200000 Hz  
Polarization: H-psi  
Gain: 10.5 dBi  
Directivity: 10.5 dBi  
Efficiency: 100%

General	
Mounting type:	magnetic
Suitable for indoor:	yes
Suitable for outdoor:	yes
Interface	
connector:	1 x SMA plug
Technical characteristics	
Frequency range:	1710 - 2700 MHz 800 - 960 MHz
Antenna gain:	3 dBi
Gain:	0 - 3 dBi
Impedance:	50 $\Omega$
Operating temperature:	-30 °C ~ 70 °C
Polarisation:	vertical
VSWR:	2.0
Physical characteristics	
Antenna type:	omnidirectional
Antenna length incl. magnetic base:	88.7 mm
Diameter magnetical base:	29 mm
Height magnetical base:	18.7 mm
Cable category:	coaxial
Cable type:	RG-174
Cable attenuation:	1.5 dB @ 1.5 GHz per meter
Cable colour:	black
Cable diameter:	2.7 mm
Cable length incl. connector:	2 m
Connector finishing:	gold-plated
Colour:	black