

Keystone Module USB Type-C™ Charging Port PD 20 W black

Description

This module by Delock provides a **USB Type-C™ Power Delivery (PD)** charging port. The USB charging port supports common fast charging protocols. Connected devices can be charged with **up to 20 W**. With its standardised dimensions it can be used for easy snap-in mounting in e.g. a Keystone patch panel, face plate or surface-mount box.



Item no. 41480

EAN: 4043619414802

Country of origin: China

Package: Box

Technical details

- Connectors:
 - 1 x USB Type-C™ female
 - 1 x 2 pin terminal block
- Input voltage: 100 - 240 V
- Input AC frequency: 50 / 60 Hz
- Input current: 0.6 A
- Output voltage / Output current / Output power:
 - USB-C™: 5.0 V / 3.0 A, 9.0 V / 2.22 A, 12.0 V / 1.67 A / max. 20,0 W
- Average active efficiency: 82.4 %
- Efficiency at low load (10 %): 76.0 %
- No-load power consumption: 0.06 W
- Short circuit protection
- For Keystone ports with 19.2 x 14.9 mm
- Colour: black
- Dimensions (LxWxH): ca. 47 x 22 x 45 mm

Package content

- Keystone module
- User manual

General

Mounting type:	Keystone module
Specification:	USB Power Delivery 3.0

Interface

Connector 1:	1 x 2 pin terminal block screw terminal
Connector 2:	1 x USB Type-C™ female

Physical characteristics

Length:	47 mm
Width:	22 mm
Height:	45 mm
Colour:	black

Power supply

Input voltage:	100 - 240 V
Input AC frequency:	50 / 60 Hz
Input current:	0.6 A
Output voltage / Output current / Output power:	5.0 V / 3.0 A / 15.0 W 9.0 V / 2.22 A / 20.0 W 12.0 V / 1.67 A / 20.0 W
Average active efficiency:	82.4 %
Efficiency at low load (10 %):	76.0 %
No-load power consumption:	0.06 W

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de

Website www.delock.de