

Magnetic Enclosure USB Type-C™ 10 Gbps for 1 x M.2 NVMe or SATA SSD

Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD in 2230 format**, and due to its magnetic bottom e.g. can be attached to the back of an iPhone 15. In addition, the enclosure can also be connected to a PC or laptop via Thunderbolt™ 3, Thunderbolt™ 4 or USB-C™.

Enable magnetic function

If your smartphone does not have a magnetic back, you can place the included metal ring between your device and the phone case. This allows the magnetic enclosure to be securely attached to your smartphone.

Combo enclosure

The big advantage of this Delock M.2 enclosure is that both **SATA and PCIe (NVMe) M.2 SSDs** can be inserted into the enclosure. The memory is **automatically recognized by the chipset** and can then be used.

SSD installation without tools

The special feature of this enclosure is that **no tools** are required to install the M.2 SSD.



Item no. 42032

EAN: 4043619420322

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
external: 1 x USB 10 Gbps USB Type-C™ female
internal: 1 x M.2 key M slot
- Chipset: Realtek RTL9210B
- Supports M.2 modules in format 2230 with key M or key B+M based on SATA or PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 10 Gbps
- LED indicator
- Metal housing
- Hot Plug, Plug & Play

- Dimensions (LxWxH): ca. 61 x 61 x 13 mm

System requirements

- Android 14.0 or above
- Chrome OS
- Linux Kernel 6.2 or above
- Mac OS 14.5 or above
- Windows 10/10-64/11
- iPad Air (4th Generation) or above
- iPhone 15 Pro or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port

Package content

- External enclosure M.2
- Cable USB-C™ male to USB-C™ male, length ca. 13 cm
- 1 x metal ring
- 2 x thermal conductive pad
- 1 x rubber nipple
- User manual

Images



General

| | |
|---|--|
| Function: | NVM Express (NVMe) Hot Plug Plug & Play |
| Supported operating system: | Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Linux Kernel 6.2 or above iPhone 15 Pro or above Android 14.0 or above Mac OS 14.5 or above |
| LED indicator: | 1 x |
| Supported module: | M.2 modules in format 2230 with key M or key B+M based on SATA or PCIe (NVMe) |
| Maximum height of the components on the module: | 1.5 mm application of double-sided assembled modules supported |

Interface

| | |
|-----------|------------------------------------|
| External: | 1 x USB 10 Gbps USB Type-C™ female |
| Internal: | 1 x M.2 key M slot |

Technical characteristics

| | |
|---------------------|------------------|
| Chipset: | Realtek RTL9210B |
| Data transfer rate: | 10 Gbps |

Physical characteristics

| | |
|-------------------|-------|
| Housing material: | metal |
| Cable length: | 13 cm |
| Length: | 61 mm |

| | |
|---------|-------|
| Width: | 61 mm |
| Height: | 13 mm |
| Colour: | grey |

Manufacturer information

| | |
|-------------|-------------------|
| Street | Beeskowdamm 13/15 |
| Postal code | 14167 |
| City | Berlin |
| Country | Deutschland |
| E-Mail | info@delock.de |
| Website | www.delock.de |