

Delock M.2 NVMe SSD Enclosure USB 40 Gbps - tool free

Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280 format, it can be connected via Thunderbolt™ 3, Thunderbolt™ 4 or USB-C™ to the PC or laptop. The **robust metal housing with cooling fins** ensures an optimum temperature of the memory.



USB 40 Gbps

Due to **USB 40 Gbps** compatibility, the Delock enclosure can be connected to Thunderbolt™ 3 and Thunderbolt™ 4 ports, as well as to all USB Type-C™ ports. The maximum data transfer rate depends on the host device.

Item no. 42033

EAN: 4043619420339

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
external:
1 x USB 40 Gbps USB Type-C™ female
internal:
1 x M.2 key M slot
- Chipset: Asmedia ASM2464PD
- Supports M.2 modules in format 2280 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 40 Gbps
- LED indicator for power and access
- Metal housing
- Hot Plug, Plug & Play
- Dimensions (LxWxH): ca. 118 x 50 x 14 mm

System requirements

- Linux Kernel 6.2 or above
- Mac OS 13.1 or above
- Windows 10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port or
- Device with a free Thunderbolt™ 4 port

Package content

- External enclosure M.2
- Cable USB-C™ male to USB-C™ male, length ca. 25 cm
- 1 x thermal conductive pad
- 1 x thermal conductive plate
- 3 x rubber nipple
- Key chain
- User manual

Images



General

Supported operating system:	Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Mac OS 13.1 or above Linux Kernel 6.2 or above
Supported module:	M.2 modules in format 2280 with key M or key B+M based on PCIe (NVMe)
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

Interface

External:	1 x USB 40 Gbps USB Type-C™ female
Internal:	1 x M.2 key M slot

Technical characteristics

Chipset:	Asmedia ASM2464PD
Data transfer rate:	40 Gbps

Physical characteristics

Housing material:	Aluminium
Length:	118 mm
Width:	50 mm
Height:	14 mm
Colour:	grey

Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin

Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de