

# USB Type-C™ 40 Gbps Enclosure for 1 x M.2 NVMe PCIe SSD with fan - tool free

## Description

This NVMe enclosure by Delock enables the installation of **an M.2 PCIe NVMe SSD in 2280, 2260, 2242 and 2230** format, it can be connected via Thunderbolt™ 3, Thunderbolt™ 4, Thunderbolt™ 5 or USB-C™ to the PC or laptop.

### USB 40 Gbps

Due to **USB 40 Gbps** compatibility, the Delock enclosure can be connected to Thunderbolt™ 3 and 4 ports, as well as to all **USB Type-C™ ports**. The maximum data transfer rate depends on the host device.

### Active cooling by fan

A **fan in the enclosure** ensures sufficient cooling of the used SSDs, so that the operation also works without problems with the closed enclosure. The fan switches on automatically when the temperature is too high.



**Item no. 42034**

EAN: 4043619420346

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - external:
    - 1 x USB 40 Gbps USB Type-C™ female
  - internal:
    - 1 x M.2 key M slot
- Chipset: Asmedia ASM2464PD
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 40 Gbps
- LED indicator for power and access
- Metal housing
- Hot Plug, Plug & Play
- Dimensions (LxWxH): ca. 121 x 60 x 17 mm

## System requirements

- Linux Kernel 6.11 or above
- Mac OS 15.3.2 or above
- Windows 10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- iPhone 15 Pro or above
- Surface Pro 9
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3, Thunderbolt™ 4 or Thunderbolt™ 5 port

---

## Package content

- External enclosure M.2
- Cable USB-C™ male to USB-C™ male, length ca. 20 cm
- User manual

---

## Images



## General

Function:	Hot Plug Plug & Play
Specification:	NVM Express (NVMe)
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 iPhone 15 Pro or above Surface Pro 9 Linux Kernel 6.11 or above Mac OS 15.3.2 or above
LED indicator:	LED indicator for power and access
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

## Interface

External:	1 x USB 40 Gbps USB Type-C™ female
Internal:	1 x M.2 key M slot

## Technical characteristics

Chipset:	Asmedia ASM2464PD
Data transfer rate:	40 Gbps

## Physical characteristics

Housing material:	metal
Length:	121 mm
Width:	60 mm
Height:	17 mm



### Manufacturer information

---

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

