

Industry Hub 10 x USB 5 Gbps Type-A with 8 kV ESD protection and DIN rail mounting

Description

This solid industry capable USB Hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by **ten USB Type-A connectors**.

Screw connection and mounting option

Each USB port has two **screw holes with M3 thread**. Appropriate cables can be plugged in and screwed into the screw holes. This ensures a secure data connection even in mobile environments.

In addition, the hub comes with **wall mounting plates** and a **DIN rail bracket**, making it perfect for installation in an industrial environment.

ESD fuse

The USB ports are protected against electrostatic discharges up to **8 kV**.

Power Supply

If necessary, an optional power supply or an optional power cable can be connected to the power socket. A **voltage between 7 - 24 V** can be applied to the terminal power connection, and to the DC connection.



Item no. 60792

EAN: 4043619607921

Country of origin: China

Package: Box

Technical details

- Connectors:
 - 1 x USB 5 Gbps Type-B female
 - 10 x USB 5 Gbps Type-A female
 - 1 x 7 - 24 V DC jack
 - 1 x 7 - 24 V 2 pin terminal power connector
- Chipset: VIA VL817
- Data transfer rate up to 5 Gbps
- Bootable
- Plug & Play
- 11 x LED indicator
- Robust metal housing
- USB ports with screw holes
- Pitch of screw hole USB Type-A: ca. 19 mm
- Pitch of screw hole USB Type-B: ca. 16.5 mm

- Thread size: M3
 - Removable wall-mount brackets
 - Power supply: Bus-powered or Self-powered
 - Flexible power supply with 7 V to 24 V
 - ESD protection up to 8 kV for all ports
 - Operating temperature: -40 °C ~ 85 °C
 - Storage temperature: -40 °C ~ 125 °C
 - Colour: black
 - Dimensions (LxWxH): ca. 177 x 67 x 28 mm
-

Specification of power connector

- DC: 7 - 24 V
 - Dimensions:
 - inside: \varnothing ca. 2.5 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 10 mm
 - terminal: 7 - 24 V
-

System requirements

- Linux Kernel 6.2 or above
 - Mac OS 13.1 or above
 - Windows 10/10-64/11
 - Windows Server 2022
 - PC or laptop with a free USB Type-A port
-

Package content

- Hub USB
- 1 x cable USB A male to USB B male, length ca. 1 m
- 2 x wall mounting brackets
- 1 x mounting for 35 mm DIN rail
- 1 x 2 pin terminal block
- Screws
- Dowel
- User manual

Images



General

| | |
|-----------------------------|--|
| Function: | Plug & Play bootable |
| Supported operating system: | Windows 10 32-Bit Windows 10 64-Bit Windows 11 Windows Server 2022 Mac OS 13.1 or above Linux Kernel 6.2 or above |
| LED indicator: | 11 x |

Interface

| | |
|--------------|---|
| Connector 1: | 1 x USB 5 Gbps Type-B female |
| Connector 2: | 10 x USB 5 Gbps Type-A female |
| Connector 3: | 1 x 7 - 24 V DC jack |
| Connector 4: | 1 x 7 - 24 V 2 pin terminal power connector |

Technical characteristics

| | |
|------------------------|-----------------|
| Chipset: | VIA VL817 |
| Data transfer rate: | 5 Gbps |
| Storage temperature: | -40 °C ~ 125 °C |
| Operating temperature: | -40 °C ~ 85 °C |

Physical characteristics

| | |
|---------|--------|
| Length: | 177 mm |
| Width: | 67 mm |
| Height: | 28 mm |
| Colour: | black |

Manufacturer information

Street Beeskowdamm 13/15

| | |
|-------------|----------------|
| Postal code | 14167 |
| City | Berlin |
| Country | Deutschland |
| E-Mail | info@delock.de |
| Website | www.delock.de |

