

Delock USB 20 Gbps M.2 Docking Station for 2 x M.2 NVMe PCIe SSD with Clone and Erase Function

Description


This M.2 docking station by Delock enables the installation of **two M.2 PCIe NVMe SSDs** and it can be connected via USB to the PC or laptop. The included USB cable allows the connection to a free **USB-C™** port.

Clone and erase function

The **clone function** enables to copy the content of one SSD to another without using a PC. No connection to the computer is required for the **erase function**. Selectively one drive or two drives can be deleted at the same time. Further **different erase modes** are available.

Ideal test equipment

The memory is simply plugged into the robust housing and can be used immediately. **No screws, tools or accessories are required**, which means that the SSD can be changed quickly.



Item no. 64300

EAN: 4043619643004

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB 20 Gbps USB Type-C™ female
 - 2 x M.2 key M slot
 - 1 x DC jack
- Chipset: JMicron JMS586U
- Supports M.2 modules with key M or key B+M based on PCIe (NVMe)
- Supports NVMe Express (NVMe)
- Data transfer rate up to 20 Gbps
- Supports UASP
- Supports TRIM
- LED indicator for power, access and copy / erase status
- Function key:
 - 1 x switch for mode
 - 1 x Clone button
 - 1 x On / Off switch
- Bootable
- Dimensions (LxWxH): ca. 80 x 80 x 33 mm
- Hot Plug, Plug & Play

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A
- Output: 12.0 V / 2.0 A / 24.0 W
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 10 mm

System requirements

- Android 13.0 or above
- Chrome OS
- Linux Kernel 6.2 or above
- Mac OS 13.1 or above
- Windows 10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port

Package content

- M.2 docking station
- Cable USB-C™ male to USB-C™ male, length ca. 1 m
- External power supply
- User manual

General

Function:	bootable Clone Function Erase function TRIM
Supported operating system:	Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Mac OS 13.1 or above Linux Kernel 6.2 or above Android 13.0 or above
LED indicator:	power, access and copy status
Supported module:	M.2 modules with key M or key B+M based on PCIe (NVMe)

Interface

Connector 1:	2 x M.2 key M slot
Connector 2:	1 x DC jack
Connector 3:	1 x USB 20 Gbps USB Type-C™ female

Technical characteristics

Chipset:	JMicron JMS586U
Data transfer rate:	20 Gbps

Physical characteristics

Housing material:	Plastic
Length:	80 mm
Width:	80 mm
Height:	33 mm

Colour:	black
---------	-------

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de