

USB 20 Gbps M.2 Docking Station for 4 x M.2 NVMe PCIe SSD with Clone and Erase Function

Description

This M.2 docking station by Delock enables the installation of **four M.2 PCIe NVMe SSDs** and can be connected via USB to the PC or laptop. The included USB cable allows the connection to a free USB-C™ port.

Clone and erase function

The **clone function** enables to copy the content of one SSD to another without using a PC. This M.2 docking station allows cloning up to three SSDs simultaneously. No connection to the computer is required for the **erase function**. Selectively one drive or multiple drives can be deleted at the same time.

Efficient cooling

The robust **aluminum housing** in combination with an integrated, hinged **fan** ensures **reliable heat dissipation** and protects your SSDs from overheating.

No screws, tools or accessories are required, which means that the SSD can be changed quickly.

Ideal test equipment

The Delock 4 Bay M.2 NVMe SSD Duplicator is the perfect choice for anyone who wants to manage, clone or backup large amounts of data. With **high speed**, practical functions and easy operation, this device is ideal for professionals, technology enthusiasts and IT specialists.



Item no. 64352

EAN: 4043619643523

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB 20 Gbps USB Type-C™ female
 - 4 x M.2 key M slot
 - 1 x DC jack
- Chipset: Asmedia ASM2464PDX
- Supports M.2 modules with key M or key B+M based on PCIe (NVMe)
- Supports NVM Express (NVMe)
- Data transfer rate up to 20 Gbps
- Supports UASP
- Supports TRIM

- LED indicator for power, access and copy / erase status
 - Function key:
 - 1 x switch for fan
 - 1 x Clone button
 - 1 x Erase button
 - 1 x On / Off switch
 - 1 x 75 mm fan
 - Bootable
 - Dimensions closed (LxWxH): ca. 102 x 88 x 36 mm
 - Plug & Play
-

Power supply specification

- Power supply type: Euro wall power plug
 - Model identifier: FJ-SW0503000E
 - Input voltage: 100 - 240 V
 - Input AC frequency: 50 / 60 Hz
 - Input current: 0.6 A
 - Output voltage / Output current / Output power: 5.0 V / 3.0 A / 15.0 W
 - Average active efficiency: 81.5 %
 - Efficiency at low load (10 %): 78.2 %
 - No-load power consumption: 0.08 W
 - Cable length of power supply: ca. 1.5 m
 - Ground outside, plus inside
 - Dimensions:
 - inside: \varnothing ca. 1.3 mm
 - outside: \varnothing ca. 3.5 mm
 - length: ca. 10 mm
-


System requirements

- Android 14.0 or above
 - Linux Kernel 6.8 or above
 - Mac OS 14.5 or above
 - Windows 10/10-64/11
 - iPad Air (4th Generation) or above
 - iPad Pro (3rd Generation) or above
 - Surface Pro 7
 - Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port
-

Package content

- M.2 docking station
- Cable USB-C™ male to USB-C™ male, length ca. 30 cm
- External power supply
- User manual

Images



General

Function:	Plug & Play Clone Function Erase function TRIM UASP
Supported operating system:	Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Android 14.0 or above Mac OS 14.5 or above Linux Kernel 6.8 or above
Slot:	PCIe

Interface

Connector:	1 x USB 20 Gbps USB Type-C™ female 4 x M.2 key M slot 1 x DC jack
------------	---

Technical characteristics

Chipset:	Asmedia ASM2464PDX
Data transfer rate:	up to 20 Gbps

Physical characteristics

Length:	102 mm
Width:	88 mm
Height:	36 mm
Colour:	black

Power supply

Power supply type:	Power supply specification Euro wall power supply
Model identifier:	Power supply specification FJ-SW0503000E
Input voltage:	Power supply specification 100 - 240 V
Input AC frequency:	Power supply specification 50 / 60 Hz
Input current:	Power supply specification 0.6 A
Output voltage / Output current / Output power:	Power supply specification 5.0 V / 3.0 A / 15.0 W
Average active efficiency:	Power supply specification 81.5 %
Efficiency at low load (10 %):	Power supply specification 78.2 %
No-load power consumption:	Power supply specification 0.08 W
Power supply connector:	Power supply specification DC Stecker 3,5 mm x 1,30 mm Ground outside, plus inside
Cable length of power supply:	Power supply specification 1.5 m

Manufacturer information

Street Beeskowdamm 13/15
 Postal code 14167
 City Berlin
 Country Deutschland
 E-Mail info@delock.de
 Website www.delock.de

