

Adapter Cable OBD-2 male to Sub-D 9 pin female with screws 1.15 m

Description

The OBD-2 standard cable by Delock enables the connection of data logger and diagnostic device etc. to vehicles with on-board diagnostic port. Possible applications include e.g. vehicle monitoring or reading and resetting the fault memory via the bus systems CAN Bus, J1850 Bus as well as K/L-Lines.



1.15 m

Pin assignment

Sub-D 9 pin	OBD-II (type B)	SAE J1962 / ISO 15031-3
1	5	Signal ground
2	4	Vehicle ground
3	6	CAN High
5	14	CAN Low
4	7	ISO 9141-2, K-Line
8	15	ISO 9141-2, L-Line
6	10	J1850 Bus -
7	2	J1850 Bus +
9	16	Battery voltage

Item no. 64353

EAN: 4043619643530

Country of origin: China

Package: Zip poly bag

Please Note

The cable is not suitable for the RS-232 computer interface.

Technical details

- Connectors:
 - 1 x OBD-2 type B male
 - 1 x serial D-Sub 9 female with screws
- Insulator: PVC
- Cable gauge: 24 AWG
- Cable diameter: ca. 6.5 mm
- Cable type: UL AWM 2464 VW-1 Flame Test
- Colour: black
- Screw type: #4-40 UNC
- Operating temperature: -20 °C ~ 80 °C
- Cable length incl. connectors: ca. 1.15 m

Package content

- OBD-2 (type B) cable

Images



General

Specification:	OBD-II Specification
----------------	----------------------

Interface

Connector 1:	OBD-II Type B
Connector 2:	1 x D-Sub 9 pin female with screws

Technical characteristics

Operating temperature:	-20 °C ~ 70 °C
------------------------	----------------

Physical characteristics

Cable length:	1,15 m
Cable gauge:	24 AWG
Screw type:	#4-40 UNC
Colour:	black
Insulator:	PVC
Cable diameter:	6.5 mm
Safety of Flammability:	VW-1

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de