

USB 20 Gbps M.2 Docking Station for 2 x M.2 NVMe PCIe SSD with Clone function

Description

This M.2 docking station by Delock enables the installation of **two M.2 PCIe NVMe SSDs** and it can be connected via USB to the PC or laptop.

M.2 PCIe SSD clone function

The **clone function** enables to copy the content of one SSD to another without using a PC.

Ideal test equipment

The memory is simply plugged into the robust housing and can be used immediately. **No screws, tools or accessories** are required, which means that the SSD can be changed quickly.



Item no. 64364

EAN: 4043619643646

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB 20 Gbps USB Type-C™ female
 - 2 x M.2 key M slot
 - 1 x USB Type-C™ female (power supply)
- Chipset: JMicron JMS586U
- Supports M.2 modules with key M or key B+M based on PCIe (NVMe)
- Supports NVM Express (NVMe)
- Data transfer rate up to 20 Gbps
- Supports UASP
- Supports TRIM
- LED indicator for power, access and copy status
- Function key:
 - 1 x Clone button
 - 1 x On / Off switch
- Bootable
- Colour: black
- Cable length: ca. 25 cm
- Dimensions (LxWxH): ca. 75 x 75 x 16 mm
- Hot Plug, Plug & Play

Power supply specification

- Power supply type: Euro wall power plug
 - Model identifier: FJ-SW618SE
 - Input voltage: 100 - 240 V
 - Input AC frequency: 50 / 60 Hz
 - Input current: 0.6 A
 - Output voltage / Output current / Output power: 5.0 V / 3.0 A / 15.0 W
 - Average active efficiency: 82.5 %
 - Efficiency at low load (10 %): 81.1 %
 - No-load power consumption: 0.05 W
-

System requirements

- Android 14.0 or above
 - Chrome OS
 - Linux Kernel 6.5 or above
 - Mac OS 14.5 or above
 - Windows 10/10-64/11
 - iPad Air (4th Generation) or above
 - iPad Pro (3rd Generation) or above
 - Surface Pro 7
 - Device with a free USB Type-C™ port or with a free Thunderbolt™ 3, Thunderbolt™ 4 or Thunderbolt™ 5 port
-

Package content

- M.2 docking station
- External power supply
- Cable USB-C™ male to USB Type-A male, length ca. 80 cm (power supply)
- User manual

Images



General

Function:	Power supply specification Hot Plug Plug & Play bootable
Specification:	Power supply specification NVM Express (NVMe)
Supported operating system:	Power supply specification Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Android 14.0 or above Linux Kernel 6.5 or above Mac OS 14.5 or above
LED indicator:	Power supply specification power, access and copy status
Supported module:	Power supply specification M.2 modules with key M or key B+M based on PCIe (NVMe)

Interface

Connector:	Power supply specification 1 x USB 20 Gbps USB Type-C™ female 1 x USB Type-C™ female (power supply) 2 x M.2 key M slot
------------	--

Technical characteristics

Chipset:	Power supply specification JMicron JMS586U
Data transfer rate:	Power supply specification up to 20 Gbps

Physical characteristics

Cable length:	Power supply specification 25 cm
Length:	Power supply specification 75 mm
Width:	Power supply specification 75 mm
Height:	Power supply specification 16 mm
Colour:	Power supply specification black

Power supply

Power supply type:	Power supply specification Euro wall power supply
Model identifier:	Power supply specification FJ-SW618SE
Input voltage:	Power supply specification 100 - 240 V
Input AC frequency:	Power supply specification 50 / 60 Hz
Input current:	Power supply specification 0.6 A
Output voltage / Output current / Output power:	Power supply specification 5.0 V / 3.0 A / 15.0 W
Average active efficiency:	Power supply specification 82.5 %
Efficiency at low load (10 %):	Power supply specification 81.1 %
No-load power consumption:	Power supply specification 0.05 W

Manufacturer information

Street Beeskowdamm 13/15
Postal code 14167

City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

