Delock HDMI KVM Extender Set over Cat.6 Cable 4K 60 Hz 70 m

Description



This **HDMI extender set** by Delock can transmit high-resolution video / audio signals and an IR control signal over a single**network cable**. At **4K 60 Hz** resolution, distances of up to **70 m** are possible. The set has wide applications in conference rooms, for tele-education or on large screens.

HDMI loop output
The transmitter has an HDMI loop output, so the signal can be **cascaded** to the next extender or to a monitor.

KVM function

A **USB keyboard and mouse** can be connected to the receiver in order to send the signals to a computer connected to the transmitter.

Power over Cable (PoC)
The set supports Power over Cable (PoC), so only one device requires a power supply. The other device is **powered via the network cable** and can therefore be used more flexible.

Screwable DC connection

The power supply with screwable connector ensures a secure and reliable connection - perfect for **professional installations** to avoid accidental disconnection.

Item no. 65957

EAN: 4043619659579

Country of origin: China

Package: Retail Box

Technical details

- Connectors Transmitter:
  Input:
  1 x HDMI-A female
  1 x DC 12 V power connector screwable
  1 x USB 1.1 Type-B female
  Output:
  1 x RJ45 jack

© 2025 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

1 x HDMI-A female
- Connectors Receiver:
  Input:
  1 x RJ45 jack
  1 x DC 12 V power connector screwable
  Output:
  1 x HDMI-A female
  1 x 3.5 mm 3 pin stereo jack female (audio)
  2 x USB 1.1 Type-A female
- Service port: USB Type Micro-B female
- Transmission of audio and video signals
- Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gbps
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Supports EDID management
- HDCP and HDR support
- Supports 7.1 Surround Sound with Dolby® TrueHD and DTS-HD Master Audio™
- Supports PoC (Power Over Cable)
- Operating range up to 70 meter
- Power consumption: max. 4.2 W
- Metal housing
- Wall-mount option
- Colour: black
- Dimensions (LxWxH): ca. 90 x 68 x 22 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 12.0 V / 1.0 A / 12.0 W
- Ground outside, plus inside
- Dimensions:
  inside: ø ca. 2.1 mm
  outside: ø ca. 5.5 mm
  length: ca. 9 mm

System requirements

- HDMI cable
- One Cat.6 or Cat.6A network cable

© 2025 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Package content

- HDMI transmitter
- HDMI receiver
- Wall mounting brackets
- Power supply
- User manual

Images







Transmitter



Receiver



© 2025 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Mounting type:	Wall mounting

Interface

Connector:	1 x USB 2.0 Type-A female 1 x USB 2.0 Type-B female
Connector 1:	1 x HDMI-A female
Connector 2:	1 x RJ45 jack
Connector 3:	1 x DC jack
Connector 4:	1 x 3.5 mm 3 pin stereo jack female

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz

Physical characteristics

Housing colour:	black
Housing material:	metal

Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de

© 2025 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.