

Industrial Gigabit Ethernet Switch 5 Port RJ45 for DIN rail

Description

This **robust, industry capable** Gigabit Ethernet switch by Delock can be used to connect different network components.

Redundant power supply with 9 V to 48 V

The switch accepts two terminal power sources, allowing it to be permanently connected to multiple power sources, enabling applications that require **high availability**.



Item no. 80162

EAN: 4043619801626

Country of origin: China

Package: Box

Technical details

- Connectors:
5 x RJ45 jack for 10/100/1000 Mbps Base-T
1 x 5 pin terminal power connector
- Data transfer rate up to 1 Gbps
- Supports IEEE 802.3 / 802.3u / 802.3z / 802.3ab
- Industrial standards: IEC61000-4-2 (ESD), IEC 61000-4-4 (EFT), IEC 61000-4-5 (Surge) level 4
- Industrial standards: IEC 60068-2-6 (Vibration), IEC 60068-2-27 (Shock), IEC 60068-2-32 (Free fall)
- LEDs for status monitoring
- Redundant power supply with 9 V to 48 V
- Power consumption: max. 2.1 W
- Robust metal housing
- Fanless
- Suitable for 35 mm DIN rail
- Protection class: IP40
- Operating temperature: -40 °C ~ 85 °C
- Dimensions (LxWxH): ca. 116 x 85 x 33 mm

System requirements

- Power supply with DC 9 V - 48 V (not included)

Package content

- Switch
- User manual

Images



General

Mounting type:	DIN rail 35 mm
----------------	----------------

Interface

Connector 1:	5 x RJ45 jack
Connector 2:	1 x 5 pin terminal block

Technical characteristics

Data transfer rate:	Gigabit Ethernet up to 1 Gbps
Operating temperature:	-40 °C ~ 85 °C

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	116 mm
Width:	33 mm
Height:	85 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de