

M12 Cable X-coded 8 pin male angled downwards to RJ45 plug angled upwards S/FTP shielded 1 m blue

Description

This industrial Ethernet cable by Delock can be used to connect various components with M12 connectors, e.g. for machine control or automation.

Angled connectors

The M12 connector is angled downwards at 90°, while the RJ45 connector is angled upwards at 90°. This angled design allows for space-saving installation in confined areas such as control cabinets or machinery housings. It also reduces strain on the cable and ensures a reliable, long-lasting connection.



1 m

Item no. 81011

EAN: 4043619810116

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x M12 male X-coded 8 pin 90° downwards angled
 - 1 x RJ45 plug 90° upwards angled
- Cat.6A specification
- Shielded (S/FTP)
- Cable gauge: 26 AWG
- Cable jacket material: PUR
- Cable diameter: ca. 6.5 mm
- Operating voltage: max. 30 V
- Current: max. 0.5 A
- Operating temperature: -20 °C ~ 70 °C
- Protection class: IP67 (M12)
- Colour: blue
- Length incl. connectors: ca. 1 m

Package content

- M12 cable

Images



General

Specification:	Cat. 6A
----------------	---------

Interface

Connector 1:	1 x M12 male X-coded 8 pin 90° downwards angled
Connector 2:	1 x RJ45 plug 90° upwards angled

Technical characteristics

Operating temperature:	-20 °C ~ 70 °C
------------------------	----------------

Physical characteristics

Cable gauge:	26 AWG
Material:	PUR
Shielding:	shielded
Length:	1 m
Colour:	blue
Cable diameter:	6.5 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

