

WiFi 7 Antenna RP-SMA plug 3.1 - 3.5 dBi omnidirectional with connection cable ULA100 1 m roof mounting outdoor black

Description

This WLAN antenna by Delock allows the usage of different WLAN bands inside and outside.

WiFi 7

WiFi 7, IEEE 802.11be, is the latest wireless standard and offers significant improvements over previous generations. It is characterised by higher speeds, lower latency and improved stability, especially in environments with many connected devices. WiFi 7 utilises the 6 GHz band for more capacity and introduces new technologies such as Multi-Link Operation (MLO) and 4K QAM. It is backwards compatible and also supports the 2.4 GHz and 5 GHz bands.



Item no. 81468

EAN: 4043619814688

Country of origin: Taiwan,
Republic of China

Package: White Box

Technical details

- Connector: 1 x RP-SMA plug
- Frequency range:
2400 - 2500 MHz
5150 - 7125 MHz
- Antenna gain: 3.1 - 3.5 dBi
- Impedance: 50 Ohm
- VSWR: 2.0
- Cable type: ULA100
- Cable attenuation: 1.4 dB @ 2500 MHz per meter
- Cable colour: black
- Cable length: ca. 1 m
- Polarisation: vertical
- Operating temperature: -40 °C ~ 85 °C
- Housing material: PC
- Colour: black
- Weight: ca. 194 g
- Dimensions (LxD): ca. 50 x 78 mm

System requirements

- Device with one free RP-SMA port

Package content

- Antenna

Images



General

Mounting type:	roof mount Screw mounting with 16 mm hole diameter
Suitable for outdoor:	yes

Interface

Connector:	1 x RP-SMA plug
------------	-----------------

Technical characteristics

Frequency range:	2400 - 2500 MHz 5150 - 7125 MHz
Antenna gain:	3.1 - 3.5 dBi
VSWR:	2.0

Physical characteristics

Housing colour:	black
Weight:	194 g
Thread length:	17.4 mm
Cable category:	coaxial
Cable attenuation:	1 db @ 1500 MHz
Thread type:	5/8" - 24 UNEF - 2A
Dimensions (LxD):	50 x 78 mm
Cable diameter:	2.79 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de