Delock SFP Module 1000Base-BX SM TX 1490 / RX 1310 nm DDM

Description

This SFP module by Delock can be used to expand a Gigabit switch with a free SFP slot by an optical fibre interface.



Item no. 86230

EAN: 4043619862306

Country of origin: China

Package: White Box

Technical details

- Connectors:
  1 x SFP male
  1 x LC Simplex female
- Data transfer rate:
  Gigabit Ethernet up to 1 Gbps
- For single-mode fiber
- Fibre: 9/125 µm
- Bidirectional (BiDi)
- TX: 1490 nm wavelength
- RX: 1310 nm wavelength
- Up to 10 km
- Digital Diagnostic Monitoring Interface (DDM)
- Operating temperature: 0 °C ~ 70 °C

System requirements

- Device with a free SFP port

Package content

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2025 by Delock. All rights reserved.**

- SFP module

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2025 by Delock. All rights reserved.**

Interface

Connector:	1 x SFP plug
Connector 1:	1 x LC Simplex female

Technical characteristics

Data transfer rate:	Gigabit Ethernet up to 1 Gbps

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2025 by Delock. All rights reserved.**