Delock Serial Switch RS-232 / RS-422 / RS-485 2-port manual

Description

This RS-232 / RS-422 / RS-485 switch by Delock is a manually bidirectional switch for connecting different devices with RS-232 / RS-422 / RS-485 port. This switch offers two different applications.

1. It can be connected to two devices with RS-232 / RS-422 / RS-485 port e.g. computer or modem on one RS-232 / RS-422 / RS-485 port.

2. It can be connected to one device with RS-232 / RS-422 / RS-485 port on two RS-232 / RS-422 / RS-485 lines.



Specification

- Connectors:
  2 x serial Sub-D 9 pin female
  1 x serial Sub-D 9 pin male
- Serial male and female ports with nuts
- Signals (1:1): TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- 2 mechanical buttons
- Plastic housing
- Wallmount option
- No external power supply needed
- Dimensions (LxWxH): ca. 112 x 71 x 30 mm (without button)
- Colour: grey / black

System requirements

- A free Sub-D 9 pin interface

Package content

- Switch
- User manual

Item no. 87729

EAN: 4043619877294

Country of origin: China


Package: • Retail Box

Accessory

Images







General	
Mounting type:	Wall mounting
Specification:	RS-232 (EIA / TIA)
	RS-422 / RS-485 (EIA / TIA)
Supported operating system:	OS independent, no driver installation necessary
Switchover:	2 x Umschalttaste für Gerät 1 oder Gerät 2
Interface	
Connector 1:	1 x serial RS-232/422/485 DB9 male
Connector 2:	1 x serial RS-232/422/485 DB9 female
connector 3:	1 x serial RS-232/422/485 DB9 female
Physical characteristics	
Housing material:	Plastic
Length:	112 mm
Width:	71 mm
Height:	30 mm
Switch:	On / Off