

Delock USB 3.1 Slot Bracket with 1 x USB Type-C™ and 1 x USB Type-A Port

Description

With this slot bracket by Delock a PC can be extended by a USB Type-A and a USB Type-C™ port. At the USB Type-A port up to 5 V / 900 mA and a data transfer rate of up to 5 Gbps are available, at the USB Type-C™ port max. 20 V / 3 A and a data transfer rate of up to 10 Gbps.



Item no. 89934

EAN: 4043619899340

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - internal:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-E Key A male
 - 1 x 19 pin USB 3.0 pin header female
 - external:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
 - 1 x USB 3.0 Type-A female
- Electrical power:
 - USB Type-C™: max. 60 watt (20 V / 3 A)
 - USB Type-A: max. 4.5 watt (5 V / 0.9 A)
- Cable colour: black
- Cable length: ca. 50 cm

System requirements

- PC with one free slot
- Linux Kernel 3.10 or above

- Windows 7/7-64/8.1/8.1-64/10/10-64
- Motherboard with a free USB Key A female port
- Motherboard with a free 19 pin USB 3.0 pin header male

Package content

- Slot bracket

Images



Interface

External:	1 x USB 5 Gbps Type-A female 1 x USB 10 Gbps USB Type-C™ female
Internal:	1 x 19 pin USB 5 Gbps pin header female 1 x USB 3.2 Gen 2 key A 20 pin male

Technical characteristics

Data transfer rate:	10 Gbps 5 Gbps
---------------------	-------------------

Physical characteristics

Cable colour:	black
Cable length:	50 cm
Slot bracket:	standard