

# Delock USB 3.1 Gen 2 Slot Bracket with 2 x USB Type-C™ Ports

## Description

With this slot bracket by Delock a PC can be extended by two USB Type-C™ ports. At each port max. 20 V / 3 A and a data transfer rate of up to 10 Gbps are available.



USB 3.1 Gen 2 Key A connector

**Item no. 89935**

EAN: 4043619899357

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:  
internal: 2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-E Key A male  
external: 2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
- Voltage: max. 20 V
- Current: max. 3 A
- Cable colour: black
- Cable length: ca. 50 cm

## System requirements

- PC with one free slot
- Linux Kernel 3.10 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Motherboard with two free USB key A female ports

## Package content

- Slot bracket

---

## Images



## General

|                             |                                                                                                                            |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Form factor:                | Low Profile                                                                                                                |
| Specification:              | RS-232 (EIA / TIA)<br>PCIe 1.1                                                                                             |
| Supported operating system: | Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 7 32-Bit<br>Windows 7 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |
| Slot:                       | PCIe                                                                                                                       |

## Interface

|           |                                                                                |
|-----------|--------------------------------------------------------------------------------|
| External: | 1 x DB44<br>1 x Serial RS-232 DB9 plug<br>2 x USB 10 Gbps USB Type-C™ female   |
| Internal: | 1 x SATA 15 pin plug<br>1 x PCI Express x1, V1.1<br>2 x USB 10 Gbps key A male |

## Technical characteristics

|                        |                                                                                   |
|------------------------|-----------------------------------------------------------------------------------|
| Chipset:               | WCH384L                                                                           |
| Data transfer rate:    | 10 Gbps<br>up to 230.4 Kb/s<br>4 x up to 230,4 Kbps                               |
| FIFO:                  | 4 x 256 Byte                                                                      |
| Jumper:                | 8 x                                                                               |
| Operating temperature: | -40 °C ~ 85 °C                                                                    |
| Signal transmission:   | TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND                                        |
| Voltage:               | 5 V or 12 V can be set individually for each port through the jumper (pin 1 or 9) |
| UART:                  | 16C950                                                                            |



Data bits:

4, 5, 6, 7, 8

## Physical characteristics

|                |                                           |
|----------------|-------------------------------------------|
| Cable type:    | UL AWM Style 2464 30 AWG 80 °C 300 V VW-1 |
| Cable colour:  | black                                     |
| Cable length:  | 50 cm<br>25 cm                            |
| Pin finishing: | gold-plated                               |
| Screw type:    | #4-40 UNC                                 |
| Slot bracket:  | standard<br>Low Profile                   |
| Length:        | 94.3 mm                                   |
| Width:         | 63.3 mm                                   |
| Height:        | 14.0 mm                                   |
| Colour:        | green                                     |