

Adapter SMA jack to RP-SMA jack bulkhead 3 GHz

Description

This adapter by Delock is suitable for connecting components of radio frequency technology.



Item no. 89969

EAN: 4043619899692

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x SMA jack >
 - 1 x RP-SMA jack bulkhead
- Housing: brass gold plated
- Thread type: 1/4" - 36 UNS - 2A
- Frequency range: 3 GHz
- Impedance: 50 Ohm
- Operating temperature: -10 °C ~ 50 °C
- Dimensions (LxW): ca. 22.1 x 9.5 mm

System requirements

- Device with one free SMA or RP-SMA port

Package content

- Adapter

Interface

Connector 1:	1 x SMA jack
Connector 2:	1 x RP-SMA jack bulkhead

Technical characteristics

Frequency range:	3 GHz
Operating temperature:	-10 °C ~ 50 °C

Physical characteristics

Housing material:	brass gold plated
Length:	22.1 mm
Width:	9.5 mm
Thread type:	1/4" - 36 UNS - 2A

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de