

Adapter SMA plug to RP-SMA jack 10 GHz

Description

This adapter by Delock is suitable for connecting components of radio frequency technology.



Item no. 89973

EAN: 4043619899739

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x SMA plug >
 - 1 x RP-SMA jack
- Housing: brass gold plated
- Thread type: 1/4" - 36 UNS - 2A
- Inner thread: 1/4" - 36 UNS - 2B
- Frequency range: 10 GHz
- Impedance: 50 Ohm
- Operating temperature: -10 °C ~ 50 °C
- Dimensions (LxD): ca. 18.1 x 7.0 mm

System requirements

- Device with one free SMA or RP-SMA port

Package content

- Adapter

Interface

Connector 1:	1 x SMA plug
Connector 2:	1 x RP-SMA jack

Technical characteristics

Frequency range:	10 GHz
Operating temperature:	-10 °C ~ 50 °C

Physical characteristics

Housing material:	brass gold plated
Diameter:	HEX 8 mm , max. 7 mm
Length:	18.1 mm
Thread type:	1/4" - 36 UNS - 2A 1/4" - 36 UNS - 2B

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de