

# Fibre Optic Pigtail Fanout Cable 12 x LC-UPC Simplex male to 12 x open cable ends 1 m

## Description

The fibre optical pigtail cable by Delock is ideal for fibre optic installations in data centres, network cabinets or FTTH applications. It features 12 pre-terminated LC / UPC connectors on one side and open fibre ends on the other, ideal for precise splicing and patch panel mounting.



**Item no. 91050**

EAN: 4043619910502

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:  
12 x LC-UPC Simplex male  
12 x open wires
- Ceramic ferrule with dust protection
- Singlemode OS2 cable
- Fibre: 9/125 µm
- Return loss: 35 dB
- Smallest bending radius: 30 mm
- Cable diameter: ca. 4.8 mm
- LSZH (halogen-free)
- Operating temperature: -25 °C ~ 70 °C
- Cable length: ca. 1 m

## Package content

- Optical fiber cable

## Interface

Connector 1:	12 x LC-UPC Simplex male
Connector 2:	12 x open wires

## Technical characteristics

Operating temperature:	-25 °C ~ 70 °C
------------------------	----------------

## Physical characteristics

Material:	LSZH (halogen-free)
Length:	1 m
Cable diameter:	4.8 mm

## Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

