Delock 3.5″ USB 2.0 Card Reader 5 slot + 1 x USB 2.0 Type-A female

Description

This card reader by Delock can be installed into a **3.5" bay** of a PC and will be connected to an internal **USB 2.0 pin header male** port. It has a **five slot card reader** and enables the connection of one USB device.



Specification

• Connectors:
external:
1 x CF slot
1 x SD / MMC slot
1 x xD slot
1 x Micro SD slot
1 x MS slot
1 x USB 2.0 Type-A female
internal:
1 x 9 pin USB 2.0 pin header female
• Chipset: Realtek RTS5130
• Metal housing for installation into a 3.5″ bay
• Data transfer rate up to 480 Mbps
• Bootable
• LED indicator for the card reader for power (red) and access (green)
• Cable data:
1 x 9 pin USB 2.0 pin header female cable ca. 53 cm (incl. connector)
• Hot Swap, Plug & Play

• Supports following memory cards:
Slot 1
CF I, CF II, CF4.0, CF Ultra, CF Ultra DMA, CF Ultra II, CF Ultra III, CF Ultra IV, CF Extreme, CF Extreme III, CF Extreme IV, Microdrive, MagicStor

Slot 2
SD, SD Pro, SD Ultra, SD High Capacity (SDHC), Turbo-SD, SDHC Turbo, SD Ultra, SD Ultra II, SDHC Ultra, SDXC, SDXC Ultra, MMC-I, MMC-II, MMC plus, MMC plus Turbo, MMC 4.0, Mini SD*, Mini SDHC*, Turbo Mini SD*, MMCmobile*, RS-MMC*, RS-MMC 4.0*

Slot 3
xD, xD type M, xD type H

Slot 4
Micro SD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro

Slot 5
MS Micro, MS-Pro Micro, MS-HG Micro, MS XC-HG Micro, M2
*Adapter is required

System requirements

Item no. 91708

EAN: 4043619917082

Country of origin: China

Package: Retail Box

© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

- Linux Kernel 5.11 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC with one free 3.5″ bay
- Motherboard with a free 9 pin USB 2.0 pin header male

Package content

- 3.5″ card reader with connection cable
- Screws
- User manual

Images









© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Function:	Hot Swap
	Plug & Play
Supported operating system:	Windows 10 32-bit
	Windows 10 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 11
	Linux Kernel 5.11 or above
LED indicator:	2 x
Interface	
External:	1 x CF slot
	1 x MS slot
	1 x Micro SD slot
	1 x SD slot
	1 x xD slot
	1 x USB 2.0 Type-A Buchse
Internal:	1 x 9 pin USB 2.0 pin header female
Technical characteristics	
Chipset:	Realtek RTS5130
Physical characteristics	
Cable length:	50 cm

© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.