Delock 3G-SDI Switch 4 in > 1 out

Description

With this Delock SDI switch, up to four SDI input sources can be connect to one SDI output device, such as an HD-SDI monitor. By pressing a button on the device, it can be switched from one source to another.



Specification

- Connectors:
  Input:
  4 x BNC female (3G-SDI)
  1 x 5 V DC jack
  Output:
  1 x BNC female (3G-SDI)
- Supported resolution:
  SD 480i, 525i and 625i
  HD 720p 24, 25, 30, 50 and 60 Hz
  HD 1080i 50, 60 Hz
  HD 1080p 24, 25, 30, 50 and 60 Hz
- Configuration and control of the device via RS232 interface
- Robust metal housing
- Power consumption: max. 3 W
- Dimensions (LxWxH): ca. 162 x 82 x 25 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
  inside: ø ca. 2.1 mm
  outside: ø ca. 5.5 mm
  length: ca. 9 mm

Package content

- 3G-SDI Switch
- Power supply

Item no. 93251

EAN: 4043619932511

Country of origin: China

Package: • White Box

Multimedia

Images





